

# ROLLSROLLER®

## TRAFFIC 600/145t

### KEY FEATURES

- Adjustable aluminum profile bed.
- Special design for mounting onto high volume of Guide sign panels.
- Removable 4 mm or 1/6in. aluminum flatbed top and cutting mat included.

**ROLLSROLLER Traffic** is designed for road sign production with high volumes of guide signs. It has a special profile bed adjustable to fit almost any extruded guide sign panels. Traffic is most often used in combination with a Light, Basic or Premium model to create a complete workflow.

MODEL NAME	ROLLSROLLER® 600/145T
Model type	Traffic
Bed length	6 000 mm / 19ft. 2in.
Bed width	1 450 mm / 4ft. 9in.
Length of working area	5 700 mm / 18ft. 8in.
Width of working area/roller width	1 400 mm / 55in.
Overall width incl. Glide beam	1 685 mm / 5ft. 7in.
Overall height incl. Glide beam	1 400 mm / 4ft. 7in.
Max. thickness of substrate	60 mm / 2 2/5in.
Work height flatbed	905 mm / 2ft. 12in.
Bed surface	Adjustable AL profiles
Removable AL Flatbed top + Cutting mat	3 000 x 1 450 mm / 9ft. 10in. X 4ft. 9in.
Illuminated bed	not available
Roll holder for Glide Beam	yes
Roll holder for bed end	yes
Wheels	6
Required air pressure	6 -8 bar / 87-116 psi
Stop static kit, cord and magnet	yes
ROLLSROLLER Scissor	yes
Weight	min 450 kg / 990 lb
Packing weight, Pallet	470 kg / 1036 lb
Packing weight, Pallet + Crates	660 kg / 1 455 lb
Packing weight, Pallet + Box	1 080 kg / 2 380 lb
Packing dimension	6 150 x 2 000 x 1 800 mm / 20ft 2in. X 6ft. 7in. X 5ft. 11in.
Warranty	2 years
Owner's Manual (Bruksanvisning i Original)	Yes (da, de, en, es, fr, sv)
Adjustable work height 750 - 1 100 mm / 2ft. 3in. - 3ft. 7in.	not available
Machine feet	6



**ROLLSROLLER®**  
FLATBED APPLICATOR

info@rollsroller.se  
rollsroller.se  
+46 54 770 70 10

Patented product developed and manufactured by ROLLSSROLLER AB in Sweden.